

External Ø mm	Standard Length mm	Packing Unit	Wall Thickness mm	Tolerance External Ø	Tolerance Thickness (in mm)
5	2000	50	1	± 0,3mm	± 0,20
7	2000	50	1	± 0,3mm	± 0,20
8	2000	25	2	± 0,3mm	± 0,20
10 Ø	2000	25	1,5/2/3	± 0,3mm	± 0,20/0,25/0,30
12 Ø	2000	25	1/2/3	± 0,3mm	± 0,20/0,25/0,30
13 NEW	2000	25	1,5/2/3	± 0,3mm	± 0,20/0,25/0,30
15 Ø	2000	25	1/2/2,5/3	± 0,3mm	± 0,20/0,25/0,30/0,35
16	2000	25	2	± 0,3mm	± 0,25
18 NEW	2000	25	2/3	± 0,3mm	± 0,25/0,30
20 Ø	2000	5	1/2/3	± 0,3mm	± 0,20/0,25/0,30
22 NEW	2000	5	2/3	± 0,3mm	± 0,25/0,30
24 NEW	2000	5	2/3	± 0,5mm	± 0,25/0,30
25 Ø	2000	5	2/3	± 0,5mm	± 0,25/0,30
26 NEW	2000	5	2/3	± 0,5mm	± 0,25/0,30
28	2000	5	2/3	± 0,5mm	± 0,25/30
30 Ø	2000	5	2/3/4/5	± 0,5mm	± 0,25/0,30/0,35/0,40
32 NEW	2000	5	2/3/4/5	± 0,5mm	± 0,25/0,30/0,35/0,40
34 NEW	2000	5	2/3/4/5	± 0,5mm	± 0,25/0,30/0,35/0,40
36 NEW	2000	5	2/3/4/5	± 0,5mm	± 0,25/0,30/0,35/0,40
38	2000	5	3	± 0,5mm	± 0,30
40 Ø	2000	1	2/3/4/5	± 0,8mm	± 0,25/0,30/0,35/0,40
44 NEW	2000	1	2/3/4/5	± 0,8mm	± 0,25/0,30/0,35/0,40
45 NEW	2000	1	2/3	± 0,8mm	± 0,25/0,30
50 Ø	2000	1	2/3/4/5	± 0,8mm	± 0,25/0,30/0,35/0,40
56 NEW	2000	1	2/3/4/5	± 0,8mm	± 0,25/0,30/0,35/0,40
60 Ø	2000	1	2/3/4/5	± 0,8mm	± 0,25/0,35/0,35/0,40
64 NEW	2000	1	2/3/4/5	± 0,8mm	± 0,25/0,35/0,35/0,40
70 Ø	2000	1	2/3/4/5	± 0,8mm	± 0,30/0,35/0,40/0,45
76 Ø NEW	2000	1	3/4/5	± 0,9mm	± 0,35/0,40/0,45
80 Ø	2000	1	2/3/4/5	± 0,9mm	± 0,30/0,35/0,40/0,45
90 Ø	2000	1	3/4/5	± 0,9mm	± 0,35/0,40/0,45
100 Ø	2000	1	2/3/4/5	± 1,2mm	± 0,30/0,35/0,40/0,45
110 Ø	2000	1	3/4/5	± 1,2mm	± 0,35/0,40/0,45
120 Ø NEW	2000	1	2/3/4/5	± 1,2mm	± 0,30/0,35/0,40/0,45
125	2000	1	3/4/5	± 1,3mm	± 0,35/0,45
130 Ø	2000	1	3/4/5	± 1,3mm	± 0,35/0,40/0,50
133 Ø	2000	1	3/5	± 1,3mm	± 0,35/0,50
134 NEW	2000	1	3/4/5	± 1,3mm	± 0,35/0,40/0,50
150 Ø	2000	1	3/4/5	± 1,5mm	± 0,40/0,45/0,50
160 Ø NEW	2000	1	3/4/5	± 1,5mm	± 0,40/0,45/0,50
170 NEW	2000	1	3/4/5	± 1,5mm	± 0,40/0,45/0,50
180 Ø NEW	2000	1	3/4/5	± 1,5mm	± 0,40/0,50/0,55
200 Ø	2000	1	3/4/5	± 2,0mm	± 0,40/0,50/0,55
220 NEW	2000	1	3	± 2,0mm	± 0,40
230	2000	1	4/5	± 2,0mm	± 0,50/0,55
250 Ø NEW	2000	1	3/4/5	± 2,0mm	± 0,40/0,50/0,55